



2826  
PATENT APPLICATION  
Attorney Docket No. 9903-045

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Sang-Ho Ahn, et al.

Serial No. 10/008,704

Examiner: Tran, Tan N

Filed: December 6, 2001

Group Art Unit: 2826

For: ULTRA-THIN SEMICONDUCTOR PACKAGE DEVICE AND  
METHOD FOR MANUFACTURING THE SAME

TRANSMITTAL LETTER

Assistant Commissioner for Patents  
Washington, D.C. 20231

Enclosed for filing in the above-referenced application are the following:

Response to Restriction Requirement and Amendment to Specification  
 Return Post Card



20575

PATENT TRADEMARK OFFICE

Respectfully submitted,

MARGER JOHNSON & McCOLLOM, P.C.

Alan T. McCollom  
Reg. No. 28,881

MARGER JOHNSON & McCOLLOM, P.C.  
1030 SW Morrison Street  
Portland, OR 97205  
503-222-3613

I HEREBY CERTIFY THAT THIS COR-  
RESPONDENCE IS BEING DEPOSITED  
WITH THE UNITED STATES POSTAL  
SERVICE AS FIRST CLASS MAIL IN AN  
ENVELOPE ADDRESSED TO:

COMMISSIONER OF PATENTS AND  
TRADEMARKS, WASHINGTON D.C.  
20231

ASSISTANT COMMISSIONER FOR  
PATENTS, WASHINGTON D.C. 20231

ASSISTANT COMMISSIONER FOR  
TRADEMARKS, 2900 CRYSTAL DRIVE.  
ARLINGTON VA 22202-3513

ON 8-5-02



PATENT APPLICATION  
Attorney Docket No.9903-045

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Sang-Ho Ahn, et al.

Serial No. 10/008,704

Examiner: Tran, Tan N

Filed: December 6, 2001

Group Art Unit: 2826

For: ULTRA-THIN SEMICONDUCTOR PACKAGE DEVICE AND  
METHOD FOR MANUFACTURING THE SAME

Assistant Commissioner for Patents  
Washington, D.C. 20231

RECEIVED  
TECHNOLOGY CENTER 2800  
AUG 20 2002

# 6/a  
9/5/02  
Jwm

**RESPONSE TO RESTRICTION REQUIREMENT AND AMENDMENT TO THE  
SPECIFICATION**

Responsive to the Restriction Requirement, dated July 15, 2002, Applicant hereby  
elects Group I (claims 1-29 and 50-53), without traverse.

IN THE SPECIFICATION

On page 1, line 18-21, please replace the paragraph as follows:

*a)* Fig. 1 is a cross-sectional view of a conventional IC device in which semiconductor  
chips are mounted on both sides of a lead frame in order to improve a mounting density of the  
package. This package structure is disclosed, for instance, in Japanese Utility Model  
Publication No. 62-147360.